



Source: Consumer Survey Report 2019
Consumer's preference in Thailand
Retail volume value in 2019: 2019-2020



U-MATCH

FIXED-SPEED



◆ CASSETTE TYPE



◆ DUCT TYPE



◆ FLOOR CEILING TYPE



◆ OUTDOOR UNIT

รับประกัน



Remote Control



Wireless remote controller
รุ่น YAP1F6 ฿32
ใช้สำหรับ
- Floor ceiling Type



Wireless remote controller
รุ่น YAW1F9 ฿410a
ใช้สำหรับ
- Floor ceiling Type
- Cassette Type



Wired remote controller
รุ่น XK117 ฿410a
ใช้สำหรับ
- Duct Type

หลากหลายฟังก์ชันเพื่อความสบาย



• Washable Filter



• Easier Maintainability



• Quality Motor



• Horizontal Swing



• Inner Groove Copper



• Compact Design



• Wide Operation range



• Turbo Function



• Child Lock



• Auto Clean



• Self Diagnosis



• High Efficiency



• Wide Voltage range



• High ESP

Cassette-Type			
Indoor unit	Model	GU140T/A-K	GU160T/A-K
Cooling capacity	Btu/hr	48,100	51,200
Maximum Power input	Watt	5,600	5,200
Maximum Current input	A	11.20	10.30
SEER / (EER)	Btu / Wh	8.59	9.85
EGAT NO.5		-	-
Noise level (Super-High/Hight/Middle/Low)	dB(A)	54/57/47/45	55/51/47/45
Air Flow Volume	CFM	1,177	1,117
Outline Dimension (WxDxH)	mm	840x840x290	840x840x290
Package Dimension (WxDxH)	mm	933x903x335	933x903x335
Net Wight / Gross Weight	kg	34/41	34/41
Panel	Model	TF06	
Outline Dimension (WxDxH)	mm	950x950x52	
Package Dimension (WxDxH)	mm	1,033x1,038x112	
Net Wight / Gross Weight	kg	6.0/9.5	

Duct-Type			
Indoor unit	Model	GU140PH/A-K	GU160PH/A-K
Cooling capacity	Btu/hr	48,100	54,600
Maximum Power input	Watt	5,250	5,350
Maximum Current input	A	10.50	10.60
SEER / EER	Btu / Wh	9.16	10.21
EGAT NO.5		-	-
Noise level (Super-High/Hight/Middle/Low)	dB(A)	45/44/41/37	47/45/40/37
Air Flow Volume	CFM	1,295	1,471
External Static Pressure (Rated)	Pa	50	50
External Static Pressure (Range)	Pa	0-150	0-150
Outline Dimension (WxDxH)	kg	1,400x700x300	1,400x700x300
Package Dimension (WxDxH)	mm	1,601x813x365	1,601x813x365
Net Wight / Gross Weight	kg	52/59	54/61

Floor ceiling-Type			
Indoor unit	Model	GU140ZD/A-K	GU160ZD/A-K
Cooling capacity	Btu/hr	48,100	54,600
Maximum Power input	Watt	5,200	5,300
Maximum Current input	A	10.40	10.50
SEER / (EER)	Btu / Wh	9.25	10.30
EGAT NO.5		-	-
Noise level (Super-High/Hight/Middle/Low)	dB(A)	54/53/52/51	54/53/52/51
Air Flow Volume	CFM	1,295	1,471
Outline Dimension (WxDxH)	mm	1,570x665x235	1,570x665x235
Package Dimension (WxDxH)	mm	1,729x770x300	1,729x770x300
Net Wight / Gross Weight	kg	43/50	45/52

Floor ceiling-Type			
Indoor unit	Model	GULD18ZD/C-K(P)	GULD24ZD/C-K(P)
Cooling capacity	Btu/hr	18,109	24,996
Maximum Power input	Watt	1,454	2,002
Maximum Current input	A	6.72	9.23
SEER / (EER)	Btu / Wh	13.20	13.24
EGAT NO.5		-	-
Noise level (Super-High/Hight/Middle/Low)	dB(A)	49/48/46/40	49/48/46/44
Air Flow Volume	CFM	647/618/500/382	942/883/824/706
Outline Dimension (WxDxH)	mm	870*665*235	1,200*665*235
Package Dimension (LxWxH)	mm	973*770*300	1,303*770*300
Net Wight / Gross Weight	kg	25/30	32/38
Power Source		Indoor	

Outdoor Unit			
Outdoor Unit	Model	GUL140W/A-M	GUL160W/A-M
Power Supply	V/Ph/Hz	380-415/3Ph/50Hz	
Refrigerant	type	R410a	
Refrigerant Charging	kg	2.95	3.10
Connecting Pipe Inch. (mm)	Liquid	3/8"(9.52)	3/8"(9.52)
	Gas	5/8"(15.8)	5/8"(15.8)
Sound Pressure Level	dB(A)	57	57
Air Flow Volume	CFM	3,472	3,472
Outline Dimension (WxDxH)	mm	940x460x820	940x460x820
Package Dimension (WxDxH)	mm	1,083x573x973	1,083x573x973
Net weight / Gross weight	kg	93/103	95/105
Net Distance (Height/Length)	m	30/50	30/50
Power Source		Outdoor	

Outdoor Unit			
Outdoor Unit	Model	GUL140W/A-M	GUL160W/A-M
Power Supply	V/Ph/Hz	380-415/3Ph/50Hz	
Refrigerant	type	R410a	
Refrigerant Charging	kg	2.95	3.10
Connecting Pipe Inch. (mm)	Liquid	3/8"(9.52)	3/8"(9.52)
	Gas	5/8"(15.8)	5/8"(15.8)
Sound Pressure Level	dB(A)	57	57
Air Flow Volume	CFM	3,472	3,472
Outline Dimension (WxDxH)	mm	940x460x820	940x460x820
Package Dimension (WxDxH)	mm	1,083x573x973	1,083x573x973
Net weight / Gross weight	kg	93/103	95/105
Net Distance (Height/Length)	m	30/50	30/50
Power Source		Outdoor	

Outdoor Unit			
Outdoor Unit	Model	GUL140W/A-M	GUL160W/A-M
Power Supply	V/Ph/Hz	380-415/3Ph/50Hz	
Refrigerant	type	R410a	
Refrigerant Charging	kg	2.95	3.10
Connecting Pipe Inch. (mm)	Liquid	3/8"(9.52)	3/8"(9.52)
	Gas	5/8"(15.8)	5/8"(15.8)
Sound Pressure Level	dB(A)	57	57
Air Flow Volume	CFM	3,472	3,472
Outline Dimension (WxDxH)	mm	940x460x820	940x460x820
Package Dimension (WxDxH)	mm	1,083x573x973	1,083x573x973
Net weight / Gross weight	kg	93/103	95/105
Net Distance (Height/Length)	m	30/50	30/50
Power Source		Outdoor	

Outdoor Unit			
Outdoor Unit	Model	GUL18W/NhC-K(P)	GUL24W/NhC-K(P)
Power Supply	V/Ph/Hz	220-240/1Ph/50Hz	
Refrigerant	type	R32	
Refrigerant Charging	gram	950	1,200
Connecting Pipe Inch. (mm)	Liquid	1/4"(6.35)	3/8"(9.52)
	Gas	1/2"(12.7)	5/8"(15.8)
Sound Pressure Level	dB(A)	51	52
Air Flow Volume	CFM	1,412	1,766
Outline Dimension (WxDxH)	mm	818x320x596	892x340x698
Package Dimension (LxWxH)	mm	948x420x645	1,029x458x750
Net weight / Gross weight	kg	41/44	50/54
Net Distance (Height/Length)	m	15/30	15/30